

Project Name:	
Type:	

MSEL-800

Exit Sign
New York Certified Solutions

PRODUCT FEATURE

HOUSING

- Compact and decorative design
- Aluminum housing with high grade acrylic panel
- Replaceable acrylic EXIT panel
- Removable directional indicators
- Single and double face universal design
- Removable front cover for easy installation and maintenance
- 8" height red exit sign
- Single and double face optional
- Suitable for damp location
- LynxEM® Wireless testing and reporting system are available.



ELECTRICAL

- 120/277VAC Dual voltage operation
- Test switch and charge rate indicator
- Self-test and Self-diagnostics function is available for battery backup model
- Fully automatic, solid-state charger
- Brown out circuit with overload and short-circuit protection

MOUNTING

- Universal mounting including wall mount, end mounting, ceiling mounting

LISTING

- Suitable for use in 10°C - 40°C ambient temperature, suitable for damp location
- UL listed meets or exceed all requirement in NFPA 70, NFPA 101 life safe code

WARRANTY

- See [Limited Warranty Policy](#) for more additional information

RELATED PRODUCTS

- [RCEL-8000 Edge lit Combo](#)
- [SCEL-8000 Emergency Light](#)
- [MS3 - NY Certified Solutions](#)
- [MEX-800 NY Certified Solutions](#)

ORDER INFORMATION: EXAMPLE: MSEL-800-D-R-M-BLANK-WH-BLANK

MODEL	SERIES	NUMBER OF FACE	LETTERING	BACKGROUND	FUNCTION	HOUSING COLOR	PANEL
MSEL	800 Battery backup 810 AC only	S Single face D Double face	R Red	C Clear M Mirror	BLANK Standard circuit CT Self-Diagnostics ZD Wireless Reporting LynxEM® Control	AL Aluminum WH White	B LANK Standard type U Including single and double face panel For universal

Project Name:	
Type:	

MSEL-800

Exit Sign
New York Certified Solutions

MODEL LIST AND ELECTRICAL RATING

MODEL	NUMBER OF FACE	LETTERING COLOR	TEST FACILITY	BATTERY	RECHARGE TIME	EMERGENCY DURATION	OUTPUT		
							VOLTAGE	Hz	POWER
MSEL-810SR(C/W/M)-x*	Single face	Red	N/A	N/A	N/A	90min	120/277	60	2W
MSEL-810dr(m/w)	Double face	Red	N/A	N/A	N/A	90min	120/277	60	2W
MSEL-800SR(C/W/M)-x	Single face	Red	Manual test	Ni-Cad 4.8V300mA	24H	90min	120/277	60	3W
MSEL-800dr(M)	Double face	Red	Manual test	Ni-Cad 4.8V300mA	24H	90min	120/277	60	3W
MSEL-800SR(C/W/M)-CT-x	Single face	Red	Self-test/ Self-diagnostics	Ni-Cad 3.6V300mA	24H	90min	120/277	60	4W
MSEL-800DR(M)-CT	Double face	Red	Self-test/ Self-diagnostics	Ni-Cad 3.6V300mA	24H	90min	120/277	60	4W

Note:
x*: descript for panel option
Blank: Single face
U: Including single & double face suitable for universal

PACKAGING

Q'TY : 6 PCS
 N.W : 10.2 KGS
 G.W : 11.2 KGS
 MEA'S : 1. CUFT

